

AMENDMENTS TO THE CLAIMS:

The listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

Claim 1 (currently amended) A filter comprising an intermetallic compound reagent which binds with a gaseous component of a gas stream to remove said gaseous component from said gas stream.

Claim 2 (currently amended) The filter according to claim 1, wherein the filter comprises a cigarette filter attached to a tobacco rod by tipping paper or the intermetallic compound reagent is incorporated in one or more cigarette filter parts selected from the group consisting of shaped paper insert, a plug, a space, or a free-flow sleeve.

Claim 3 (currently amended) The filter according to claim 1, wherein the intermetallic compound reagent selectively binds to unsaturated hydrocarbons in the gas stream.

Claim 4 (currently amended) The filter according to claim 1, wherein the intermetallic compound reagent comprises nanometer or micrometer size clusters of a transition metal or alloy containing a transition metal or a transitional metal salt.

Claim 5 (original) The filter according to claim 1, wherein the gaseous component to be removed from said gas stream is 1,3-butadiene, isoprene and/or toluene.

Claim 6 (currently amended) The filter according to claim 4, wherein said intermetallic compound reagent is incorporated in cigarette filter paper located within a free-flow filter, the filter paper optionally having a three-dimensional shape and/or the filter paper being a liner on the interior of a hollow tubular element.

Claim 7 (currently amended) The filter according to claim 1, wherein said intermetallic compound reagent is incorporated with cellulose acetate fibers and/or polypropylene fibers forming a plug or a free-flow filter element.

Claim 8 (currently amended) The filter according to claim 4, wherein said intermetallic compound reagent is incorporated in or on a support material.

Claim 9 (original) The filter according to claim 8, wherein said support material comprises silica gel, porous carbon or a zeolite.

Claim 10 (original) The filter according to claim 4, wherein said transition metal includes iron and/or titanium.

Claim 11 (currently amended) The filter according to claim 1, wherein said intermetallic compound reagent comprises nanometer or micrometer size clusters of an iron aluminide or a titanium aluminide.

Claim 12 (currently amended) The filter according to claim 1, wherein a metal atom of the intermetallic compound reagent binds to a C-H bond and/or a C-C bond of the gaseous component.

Claim 13 (currently amended) A method of manufacturing a filter which is useful for removing a gaseous component of a gas stream, comprising steps of:

incorporating an intermetallic compound reagent in a filter, the intermetallic compound reagent being effective to bind with a gaseous component of a gas stream sufficiently to selectively remove the gaseous component from the gas stream.

Claim 14 (currently amended) The method according to claim 13, further comprising attaching the filter to a tobacco rod with tipping paper or the intermetallic compound reagent is incorporated in one or more cigarette filter parts selected from the group consisting of shaped paper insert, a plug, a space, or a free-flow sleeve.

Claim 15 (currently amended) The method according to claim 14, further comprising a step of attaching the filter paper within a free-flow filter of a cigarette such as by forming said filter paper into a three-dimensional shape or attaching said filter paper as a liner on

the interior of a hollow tubular element or combining said intermetallic compound reagent with fibers and forming a filter element from said intermetallic compound reagent and fibers or combining said intermetallic compound reagent with cellulose and/or polypropylene fibers and forming a plug or free-flow filter element or incorporating said intermetallic compound reagent in a cavity of said filter.

Claim 16 (currently amended) The method according to claim 13, wherein the intermetallic compound reagent is effective for removing unsaturated hydrocarbons including 1,3-butadiene, isoprene and/or toluene from the gas stream.

Claim 17 (currently amended) The method according to claim 13, wherein the intermetallic compound reagent comprises nanometer or micrometer size clusters of a transition metal or alloy containing a transition metal or a transitional metal salt.

Claim 18 (currently amended) The method according to claim 17, further comprising a step of loading said intermetallic compound reagent in or on a support material forming a filter element of the filter.

Claim 19 (original) The method according to claim 18, wherein the support material comprises silica gel, porous carbon or a zeolite.

Claim 20 (currently amended) A method of removing a gaseous component from a gas stream, comprising passing the gas stream in contact with a filter comprising an intermetallic compound reagent which binds with a gaseous component of the gas stream and removes said gaseous component from the gas stream.

Claim 21 (currently amended) The method according to claim 20, further comprising steps of forming the gas stream by burning tobacco and directing tobacco smoke through the filter such that the component of the gas stream to be removed is brought into contact with the intermetallic compound reagent and prevented from reentering the gas stream.

Claim 22 (currently amended) The method according to claim 21, wherein the intermetallic compound reagent is incorporated in one or more cigarette filter parts selected from the group consisting of filter paper, shaped paper insert, a plug, a space, or a free-flow sleeve, the tobacco smoke being passed through the one or more filter parts.

Claim 23 (currently amended) The method according to claim 20, wherein the intermetallic compound reagent is effective to selectively remove unsaturated hydrocarbons present in the gas stream.

Claim 24 (currently amended) The method according to claim 20, wherein the intermetallic compound reagent comprises nanometer or micrometer size clusters of a transition metal or alloy containing a transition metal or a transitional metal salt.

Claim 25 (original) The method according to claim 20, wherein the filter removes 1,3-butadiene, isoprene and/or toluene from the gas stream.

Claim 26 (currently amended) The method according to claim 20, wherein the intermetallic compound reagent is incorporated in or on a support material selected from the group consisting of silica gel, porous carbon or a zeolite.

Claim 27 (original) The method according to claim 26, wherein said silica gel has an average particle diameter of at least 10 μm or said silica gel is in the form of particles having a mesh size of at least 60 and the gas stream is passed through a mass of particles of said silica gel.

Claim 28 (original) The method according to claim 26, wherein said silica gel is incorporated with cellulose acetate fibers and/or polypropylene fibers and the gas stream is a smoke stream from a burning cigarette.

Claim 29 (currently amended) The method according to claim 20, wherein a metal atom of the intermetallic compound reagent binds to a C-H bond and/or a C-C bond of the gaseous component.

Claim 30 (currently amended) The filter according to Claim 1, wherein the intermetallic reagent is a non-oxide intermetallic compound reagent or a crystalline intermetallic compound reagent.

Claim 31 (currently amended) The method according to Claim 13, wherein the intermetallic compound reagent is a non-oxide intermetallic compound reagent or a crystalline intermetallic compound reagent.

Claim 32 (previously presented) A filter comprising a metal reagent which binds with a gaseous component of a gas stream to remove said gaseous component from said gas stream, wherein the metal reagent comprises nanometer or micrometer size clusters of a transition metal or alloy containing a transition metal or a transitional metal salt and the metal reagent is incorporated in cigarette filter paper located within a free-flow filter, the filter paper optionally having a three-dimensional shape and/or the filter paper being a liner on the interior of a hollow tubular element.

Claim 33 (currently amended) A method of removing a gaseous component from a gas stream, comprising passing the gas stream in contact with a cigarette filter comprising a metal reagent which binds with a gaseous component of the gas stream and removes said gaseous component from the gas stream, wherein the metal reagent is incorporated in or on a support material selected from the group consisting of silica gel, porous carbon or and a zeolite and said silica gel has an average particle diameter of at least 10 μm , or said silica

gel is in the form of particles having a mesh size of at least 60 and the gas stream is passed through a mass of particles of the silica gel.

Claim 34 (currently amended) A method of removing a gaseous component from a gas stream, comprising passing the gas stream in contact with a filter comprising a metal reagent which binds with a gaseous component of the gas stream and removes said gaseous component from the gas stream, wherein the metal reagent is incorporated in or on a support material selected from the group consisting of silica gel, porous carbon or and a zeolite and said silica gel is incorporated with cellulose acetate fibers and/or polypropylene fibers, and the gas stream is a smoke stream from a burning cigarette.

Claim 35 (new) The filter according to claim 1, wherein the filter is a cigarette filter.

Claim 36 (new) A cigarette, comprising:

the cigarette filter according to claim 35; and
a tobacco rod attached to the filter by tipping paper.

Claim 37 (new) The filter according to claim 4, wherein the filter is a cigarette filter.

Claim 38 (new) A cigarette, comprising:

the cigarette filter according to claim 37; and
a tobacco rod attached to the filter by tipping paper.

Claim 39 (new) The filter according to claim 11, wherein the filter is a cigarette filter.

Claim 40 (new) A cigarette, comprising:

the cigarette filter according to claim 39; and

a tobacco rod attached to the filter by tipping paper.